
Flanged diesel engine pumps





caprari















Ideal for

PROFESSIONAL AGRICULTURE

WATER SUPPLY

MEC-AG

MEC-MG MEC-MG HT





The MEC-AG series are single-stage centrifugal horizontal shaft pumps designed for direct flanged coupling to diesel engines. The new MEC-AG series now features a modular structure for coupling to the engine with flange-flywheel size SAE4. They are also available in monobloc version with SAE3 flange and the "light" version with not supported shaft with SAE4 flange.

The MEC-AG represent the single impeller version of the MEC-MG: they are constructed with sturdy castings with high structural resistance, have oil lubrication, guarantee reliability and durability.

PERFORMANCE

Capacity	up to 135 l/s
Head	up to 115 m
Power	up to 145 kW







New Easy Fit stuffing box

This innovative system, available for all the MEC-MG and MEC-AG pumps series, allows you to remove the stuffing box leaving the pump in place, access the packing seal and replace it directly in the field.

The Easy Fit geometry and materials make the device practical, lightweight and sturdy at the same time; cataphoresis-treated components are resistant to oxidation.

Flanged diesel engine pumps


The MEC-MG are multistage centrifugal horizontal shaft pumps designed for direct flanged coupling to diesel engines. The new MEC-MG series features a modular structure enabling a support that allows connection to the motor with size SAE4 flange-flywheel. Also available the monobloc support version with SAE3 flange. The very robust structure allows the use of these pumps in extremely heavy duty conditions and for a long time. The MEC-MG range has oil lubrication that allows high heat dissipation capacity and ease of maintenance.

PERFORMANCE


Capacity	up to 100 l/s
Head	up to 195 m
Power	up to 150 kW

MEC-MG

MEC-MG HT HIGH TECH HIGH TORQUE



- LARGE PORTS
 Easy access to the sealing area
- NEW STEEL EASY FIT Splittable in two parts and easy to remove
- 3 NEW GORE-TEX GLAND PACKING It guarantees excellent heat dissipation
- DOUBLE IMPELLER SEAL RINGS
 Replaceable to regenerate the thicknesses and guarantee performance over time
- PUMP SHAFT PROTECTED BY A CHROMED STEEL BUSH High corrosion resistance
- NEW GUARDS ON THE SEAL'S PORTS REMOVABLE FROM THE OUTSIDE Easy maintenance
- NEW SUPPORT: MODULAR SYSTEM
 Widely dimensioned bearing support which guarantees high rigidity
 Connection support with SAE3 or SAE4 flange
- NEW COUPLING GUARDS THAT CAN BE REMOVED WITHOUT DISASSEMBLING THE PUMP Easy maintenance and coupling



- PUMP SHAFT PROTECTED BY A STAINLESS STEEL BUSH High corrosion resistance
- SPLINED PUMP SHAFT IN STAINLESS STEEL With high yield strength and excellent resistance to fatigue
- NEW PLAIN BEARING
 Ensures greater shaft guide on the inlet side
- NEW GORE-TEX GLAND PACKING
 It guarantees an excellent heat dissipation
- 5 NEW STEEL EASY FIT Splittable in two parts and easy to remove
- NEW CYLINDRICAL ROLLER BEARING High load capacity
- 7 HIGH PERFORMANCE MECHANICAL SEAL On request

Boosting and Distribution of surface water Wastewater Transport and Treatment Water Collection and Distribution

Pump Control Technology

CAPRARI IN THE WORLD



CAPRARI SPA



BOMBAS CAPRARI S.A.



CAPRARI FRANCE SAS



CAPRARI PORTUGAL LDA



CAPRARI



CAPRARI TUNISIE S.A.



CAPRARI PUMPS (UK) LTD



CAPRARI PUMPEN GMBH



CAPRARI HELLAS S.A



CAPRARI PUMPS SHANGHAI CO. LTD.



CAPRARI PUMPS AUSTRALIA PTY LTD









